## **Technical Data**



# Australian Chemicals & Coatings Pty Ltd

ABN: 92 884 104 142

69 Quantum Close, Dandenong South VIC 3175

Ph: +61 (03) 9799 9833 Fax: +61 (03) 9799 9033

sales@auschem.com.au

www.auschem.com.au

#### WARNING:

# This chemical is formulated for industrial use only

Contact with skin or clothing or other improper handling or use of this product may result in bodily harm or other damage. Before using or mixing the contents with other substances, all labels applied to container, the applicable Technical Data Sheet and Material Safety Data Sheet should be read and specific instructions and precautions followed to assure correct use and personal safety.

# **CLASSIQUE STRIP AS-3**

#### **INTRODUCTION**

CLASSIQUE STRIP AS-3 is an acid activated stripper containing phenol/cresol that will remove epoxy and polyester powder coatings, and virtually all coatings depending on substrate.

#### **SUMMARY OF OPERATING DATA**

CLASSIQUE STRIP AS-3 is used as received at ambient temperatures. CLASSIQUE STRIP AS-3 can be sealed by adding water to top of tank to reduce evaporation.'

#### **OPERATIONAL RECOMMENDATIONS**

CLASSIQUE STRIP AS-3 penetrates the paint layer and destroys the bond between the paint and the metal. It is particularly effective in removing powder coat and epoxies from aluminium.

Immersion time is dependent on the paint and substrate type.

A cold water pressure rinse can be used to remove loosened paint. Work can be placed back into the stripper tank after rinsing. Water will not affect CLASSIQUE STRIP AS-3.

Bath volume should be maintained to allow AS-3 to strip consistently.

PASSIVATOR 2 should be used in the rinse stage to stop flash rusting.

#### **EQUIPMENT**

Stainless steel tanks are recommended, however polyethylene or polypropylene lined tanks can be used.

#### **TYPICAL PROPERTIES**

Type -Methylene chloride phenol/cresol formic acid type.

Appearance -Brown Liquid

Specific Gravity -1.22

### Bringing the Best Products to the Surface ●

Disclaimer: All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use or anything contained herein shall be constructed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.

## **Technical Data**



#### **SAFETY**

Store and use away from heat and naked flame.

Adequate ventilation should be provided.

Operators should be equipped with rubber gloves, apron, goggles or face shields.

CLASSIQUE STRIP AS-3 should be immediately flushed from the skin with water, if splashed in eyes flush profusely with cold running water for at least 15 minutes - SEEK MEDICAL ATTENTION.

Glycerine should be used on any spills that contact the skin.

# Bringing the Best Products to the Surface ●

Disclaimer: All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use or anything contained herein shall be constructed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.