

Australian Chemicals & Coatings Pty Ltd

ABN: 92 884 104 142

69 Quantum Close,
Dandenong South VIC 3175

Ph: +61 (03) 9799 9833
Fax: +61 (03) 9799 9033

sales@auschem.com.au
www.auschem.com.au

WARNING:

**This chemical is formulated
for industrial use only**

Contact with skin or clothing or other improper handling or use of this product may result in bodily harm or other damage. Before using or mixing the contents with other substances, all labels applied to container, the applicable Technical Data Sheet and Material Safety Data Sheet should be read and specific instructions and precautions followed to assure correct use and personal safety.

CLASSIQUE STRIP 72E

NON PHENOLIC HOT STRIPPER DECARBONISER & DE-RUSTER

INTRODUCTION

CLASSIQUE STRIP 72E is a new development in the field of alkaline paint stripping. It was specifically formulated to conform to the new regulations regarding air and chemical pollutants. Along with the benefits of the paint stripping it is an effective decarboniser & de-ruster. CLASSIQUE STRIP 72E does not contain any phenol or its derivatives, and is relatively odourless.

CLASSIQUE STRIP 72E was developed to strip alkyds, alkyd derivatives, phenolics, polyester powder coats, cellulose acetate, cellulose nitrates, gum resins, and fatty acid-based coatings from steel, brass, copper and magnesium. In most cases it solubilizes, and dissolves the coating, and any residual pigment is readily rinseable, other coatings can be stripped by the addition of up to 5% ADDITIVE 45P.

CLASSIQUE STRIP 72E has shown itself to be an efficient, economical and fast stripper of heavily encrusted paint hooks.

CLASSIQUE STRIP 72E when set up to run at the high end of the concentration range and at the rolling boil will effectively decarbonise and de-rust mild steel parts.

COMPOSITION

CLASSIQUE STRIP 72E is a blend of dust free, free flowing highly alkaline salts, organic biodegradable surfactants, non-toxic organic solvents, and organic chelates, all contributing to make CLASSIQUE STRIP 72E a superior hot tank paint stripper, decarboniser & de-ruster.

CLASSIQUE STRIP 72E DOES NOT CONTAIN PHENOL OR PHENOL DERIVATIVES, CYANIDES, OR CHROMATES.

● *Bringing the Best Products to the Surface* ●

Disclaimer: All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use or anything contained herein shall be constructed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.

APPLICATION

CONCENTRATION : 100 – 400 g/L

TEMPERATURE RANGE : 60 – 90°C Rolling boil

TANK : Mild Steel

TIME: Dependent upon application

MAKE UP AND PROCEEDURE:

The tank should be half filled with water and warmed up to 50 – 55°C. The required amount of CLASSIQUE STRIP 72E should then be added to the tank with continuous stirring. After all the CLASSIQUE STRIP 72E has been dissolved adjust the solution to the desired level with water and heat to operating temperature.

TESTING

1. Pipette a 5ml sample of the CLASSIQUE STRIP 72E bath into a conical flask and add 100ml of D.I. Water.
2. Add 6 drops of phenolphthalein indicator
3. Fill the burette with 1N hydrochloric acid solution.
4. While stirring the sample slowly run the 1N hydrochloric acid solution from the burette until the pink colour disappears. Record the millilitres of 1N hydrochloric acid used as A

CALCULATION: $A \times 12.6 = \text{g/L of CLASSIQUE STRIP 72E}$

HEALTH AND SAFETY

CLASSIQUE STRIP 72E is highly alkaline, and can cause severe burns. Avoid contact with skin and eyes. Avoid inhaling dust. Wear protective clothing and safety goggles. Flush exposed areas with clean cold water. In case of injury consult a physician

For further detailed information refer to CLASSIQUE STRIP 72E safety data sheet

● *Bringing the Best Products to the Surface* ●

Disclaimer: All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use or anything contained herein shall be constructed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.