# **Technical Data**



# **CLASSIQUE STRIP E200**

## HOT TANK STRIPPER

CLASSIQUE STRIP E200 is a cost effective and safe non-methylene chloridebased paint stripper that will remove industrial coatings from ferrous and non-ferrous metal surfaces. CLASSIQUE STRIP E200 is a 2- part product that is diluted in water.

Epoxy, polyurethane, polyester and acrylic enamel coatings as well as epoxy hybrid and polyester powder coatings are removed by CLASSIQUE STRIP E200.

#### **OPERATIONAL RECOMMENDATIONS**

RATIOS - 10-25% PART A	A; 10-25%	PART B or 1-2.5% PART C; REST WATER
TEMPERATURE	-	65-88°C
TANK CONSTRUCTION	-	Stainless Steel
STRIPPING TIME	-	varies according to
		film build

After the coating has been penetrated and loosened, rinsing with water will remove any residual paint. Agitation of tank is also recommended to increase speed and effectiveness

TYPE -	non-methylene chloride type mildly alkaline solvent and
	water mixture
APPEARANCE -	clear liquid until mixed and it creates a milky emulsion

### **BATH CONTROL**

Bath pH must be maintained above 11

### **CLASSIQUE STRIP E200A**

- 1. Take a 100ml stoppered graduated cylinder. Add 2 teaspoons (10ml) of salt.
- 2. Then fill to the100ml line with a sample of the bath. Shake to dissolve salt.
- 3. Stand for a couple of minutes to allow solvent layer to form on the top.
- 4. Measure the mls. of the solvent that forms = A

A = % of CLASSIQUE STRIP E200A in the bath.

### • Bringing the Best Products to the Surface •

**Disclaimer:** All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use or anything contained herein shall be constructed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.

### Australian Chemicals & Coatings Pty Ltd

ABN: 92 884 104 142

69 Quantum Close, Dandenong South VIC 3175

Ph: +61 (03) 9799 9833 Fax: +61 (03) 9799 9033

sales@auschem.com.au
www.auschem.com.au

### WARNING:

# This chemical is formulated for industrial use only

Contact with skin or clothing or other improper handling or use of this product may result in bodily harm or other damage. Before using or mixing the contents with other substances, all labels applied to container, the applicable Technical Data Sheet and Material Safety Data Sheet should be read and specific instructions and precautions followed to assure correct use and personal safety.



#### **SAFETY & HANDLING PRECAUTIONS**

- Avoid breathing vapour or mist.
- Avoid contact with eyes and skin.
- Wear gloves, goggles and protective clothing when handling.
- Use with adequate ventilation.

Refer to SDS for further safety information.

### • Bringing the Best Products to the Surface •

**Disclaimer:** All statement, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the use of or inability to use the product. No suggestion for product use or anything contained herein shall be constructed as a recommendation to use any product in infringement of any patent rights and seller and manufacturer assume no responsibility or liability for any such infringement. We recommend prospective users determine the suitability of this product through independent testing before adopting on a commercial scale.